

Safety Data Sheet

according to Regulation (EC) No 1907/2006

COROPOX EP 2221-A

Revision date: 08.06.2018

Product code: 00359-1275

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

COROPOX EP 2221-A

Art.-No.

591 0150

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Mortar

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH
Street: Heuweg 4
Place: D-06886 Wittenberg
Telephone: +49(0)3491/635-50 Telefax: +49(0)3491/635-552
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Reproductive toxicity: Repr. 2

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Suspected of damaging the unborn child.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)
1,3,5-trioxan, trioxymethylene

Signal word: Warning

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

COROPOX EP 2221-A

Revision date: 08.06.2018

Product code: 00359-1275

Page 2 of 10

| | |
|-------|--|
| H319 | Causes serious eye irritation. |
| H361d | Suspected of damaging the unborn child. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary statements

| | |
|----------------|--|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. |
| P273 | Avoid release to the environment. |
| P405 | Store locked up. |

Special labelling of certain mixtures

| | |
|--------|--|
| EUH205 | Contains epoxy constituents. May produce an allergic reaction. |
|--------|--|

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.
Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Epoxy resin formulation, contains solvents

Hazardous components

| CAS No | Chemical name | Quantity | | |
|------------|---|--------------|------------------|--------|
| | EC No | Index No | REACH No | |
| | Classification according to Regulation (EC) No. 1272/2008 [CLP] | | | |
| 25068-38-6 | Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) | | | < 90 % |
| | 500-033-5 | 603-074-00-8 | 01-2119456619-26 | |
| | Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411 | | | |
| 110-88-3 | 1,3,5-trioxan, trioxymethylene | | | < 15 % |
| | 203-812-5 | 605-002-00-0 | 01-2119487944-20 | |
| | Flam. Sol. 1, Repr. 2, STOT SE 3; H228 H361d H335 | | | |
| 1330-20-7 | Xylene (mixed isomers) | | | < 10 % |
| | 215-535-7 | 601-022-00-9 | 01-2119488216-32 | |
| | Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304 | | | |

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

COROPOX EP 2221-A

Revision date: 08.06.2018

Product code: 00359-1275

Page 3 of 10

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Summon a doctor immediately.
Never give anything by mouth to an unconscious person.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.
Suspected of damaging the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.
Ensure adequate ventilation.
Use personal protective clothing.

6.2. Environmental precautions

Clean contaminated surface thoroughly.
Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

COROPOX EP 2221-A

Revision date: 08.06.2018

Product code: 00359-1275

Page 4 of 10

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal see section 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed.
Use only in thoroughly ventilated areas.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep product and empty container away from heat and sources of ignition.
Do not smoke.
Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.
Protect against direct sun radiation.

Advice on storage compatibility

Incompatible with:
Oxidizing agents
Amines
Acids and bases.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Mortar

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|-----------|-----------------------|-----|-------------------|-----------|---------------|--------|
| 1330-20-7 | Xylene: mixed isomers | 50 | 220 | | TWA (8 h) | WEL |
| | | 100 | 441 | | STEL (15 min) | WEL |

Biological Monitoring Guidance Values (EH40)

| CAS No | Substance | Parameter | Value | Test material | Sampling time |
|-----------|-------------------------------------|-----------------------------------|--------------|---------------|---------------|
| 1330-20-7 | Xylene, o-, m-, p- or mixed isomers | methyl hippuric acid (creatinine) | 650 mmol/mol | urine | Post shift |

8.2. Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.
Wash hands before breaks and immediately after handling the product.
When using do not eat, drink or smoke.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

COROPOX EP 2221-A

Revision date: 08.06.2018

Product code: 00359-1275

Page 5 of 10

Avoid contact with skin, eyes and clothing.
Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).
Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril 735> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

No personal respiratory protective equipment normally required.
In case of insufficient ventilation or long-term effect wear suitable respiratory equipment. Filter type A-P2 (EN 141)

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|-----------------|----------------|
| Physical state: | Liquid |
| Colour: | Colourless |
| Odour: | Characteristic |

| | Test method |
|-----------|---------------|
| pH-Value: | 4,5 (200 g/l) |

Changes in the physical state

| | |
|--|------------------------|
| Melting point: | n.d. |
| Initial boiling point and boiling range: | > 110 °C DIN 53171 |
| Sublimation point: | n.a. |
| Softening point: | n.a. |
| Pour point: | n.d. |
| Flash point: | approx. 33 °C ISO 2719 |

Flammability

| | |
|-------------------------|---------------|
| Solid: | n.a. |
| Gas: | n.a. |
| Lower explosion limits: | 1,0 vol. % *) |
| Upper explosion limits: | 8,0 vol. % *) |
| Ignition temperature: | > 300 °C |

Auto-ignition temperature

| | |
|--------------------------------|---|
| Solid: | n.a. |
| Gas: | n.a. |
| Decomposition temperature: | n.d. |
| Vapour pressure: (at 20 °C) | 0,3 hPa |
| Density (at 20 °C): | approx. 1,12 g/cm ³ ISO 2811 |
| Bulk density: | n.a. |

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

COROPOX EP 2221-A

Revision date: 08.06.2018

Product code: 00359-1275

Page 6 of 10

| | |
|------------------------------------|---------------------------|
| Water solubility: (at 20 °C) | Miscible |
| Partition coefficient: | n.d. |
| Viscosity / dynamic: (at 25 °C) | 350 - 450 mPa·s DIN 53015 |
| Viscosity / kinematic: | n.d. |
| Flow time: | n.d. |
| Vapour density: | n.d. |
| Evaporation rate: | n.d. |
| Solvent separation test: | n.d. |
| Solvent content: | n.d. |

9.2. Other information

No data available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactionsReactions with acids, alkalies and oxidizing agents
Reactions with amines.**10.4. Conditions to avoid**To avoid thermal decomposition, do not overheat.
Protect against direct sun radiation.**10.5. Incompatible materials**Strong oxidizing agents
Acids and bases.
Amines**10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

LD50/oral/rat: 11400 mg/kg

LD50/dermal/rabbit: $>$ 2000 mg/kg**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye irritation.

Sensitising effectsContains epoxy constituents. May produce an allergic reaction. May cause an allergic skin reaction. (Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700))**Carcinogenic/mutagenic/toxic effects for reproduction**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

COROPOX EP 2221-A

Revision date: 08.06.2018

Product code: 00359-1275

Page 7 of 10

Suspected of damaging the unborn child. (1,3,5-trioxan, trioxymethylene)
Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

SECTION 12: Ecological information**12.1. Toxicity**

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

LC50/Oncorhynchus mykiss/96 h = 2 mg/l

EC50/Daphnia magna/48 h = 1,8 mg/l

ErC50/Scenedesmus capricornutum/72 h = 11 mg/l

12.2. Persistence and degradability

Not readily biodegradable.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

COROPOX EP 2221-A

Revision date: 08.06.2018

Product code: 00359-1275

Page 8 of 10

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1866
14.2. UN proper shipping name: Resin solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1866
14.2. UN proper shipping name: Resin solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1866
14.2. UN proper shipping name: Resin solution (Epoxy resin)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: Yes
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1866
14.2. UN proper shipping name: Resin solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III

Safety Data Sheet

according to Regulation (EC) No 1907/2006

COROPOX EP 2221-A

Revision date: 08.06.2018

Product code: 00359-1275

Page 9 of 10

Hazard label:

3



Limited quantity Passenger:

10 L

Passenger LQ:

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger:

355

IATA-max. quantity - Passenger:

60 L

IATA-packing instructions - Cargo:

366

IATA-max. quantity - Cargo:

220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC):

< 10 %

Information according to 2012/18/EU
(SEVESO III):

P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

COROPOX EP 2221-A

Revision date: 08.06.2018

Product code: 00359-1275

Page 10 of 10

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

| | |
|--------|--|
| H226 | Flammable liquid and vapour. |
| H228 | Flammable solid. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H361d | Suspected of damaging the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH205 | Contains epoxy constituents. May produce an allergic reaction. |

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)