

according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX H COMP. A

Product code: 00359-1013 Revision date: 12.05.2020 Page 1 of 9 SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier TIP TOP REMAFIX H COMP. A Art.-No. 525 0556, 525 0563 1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture Two component repair kit 1.3. Details of the supplier of the safety data sheet TIP TOP Oberflaechenschutz Elbe GmbH Company name: Street: Heuweg 4 Place: D-06886 Wittenberg Telephone: +49(0)3491/635-50 Telefax: +49(0)3491/635-552 **Responsible Department:** Responsible for the safety data sheet: sds@gbk-ingelheim.de INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a) 1.4. Emergency telephone In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111 number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Skin corrosion/irritation: Skin Irrit. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Formaldehyde, oligomeric reaction products with 1-chloro-2, 3-epoxypropane and phenol bis-[4-(2,3-epoxipropoxi)phenyl]propane **Inal word:** Warning

Signal word:

Pictograms:



Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX H COMP. A

Revision date: 12.05.2020

Product code: 00359-1013 and easy to do. Continue rinsing. Page 2 of 9

	present and easy to do. Continue rinsing
P302+P352	IF ON SKIN: Wash with plenty of water.
P362	Take off contaminated clothing.
P273	Avoid release to the environment.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture containing following substances with additives

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	GHS Classification				
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2, 3-epoxypropane and phenol			< 55 %	
	500-006-8		01-2119454392-40		
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411				
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane			< 20 %	
	216-823-5	603-073-00-2	01-2119456619-26		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products. In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water. Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting. Rinse out mouth and give plenty of water to drink. Never give anything by mouth to an unconscious person. Summon a doctor immediately. Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX H COMP. A

Revision date: 12.05.2020

Product code: 00359-1013

Page 3 of 9

4.3. Indication of any immediate medical attention and special treatment needed Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Cool containers at risk with water spray jet. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator. Ensure adequate ventilation. Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal. Clean contaminated surface thoroughly.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Use only in thoroughly ventilated areas. Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place. Protect against direct sun radiation.

Hints on joint storage

Incompatible with: Oxidizing agents, Amines, Acids and bases.



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX H COMP. A

Revision date: 12.05.2020

Product code: 00359-1013

Page 4 of 9

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Two component repair kit

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7440-44-0	Graphite, respirable	-	4		TWA (8 h)	WEL

Additional advice on limit values

This product does not contain any substances for which a Workplace Exposure Limit has been set in concentrations above the limits.

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours. Wash hands before breaks and immediately after handling the product. When using do not eat, drink or smoke. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166). Eye wash bottle with pure water (EN 15154).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Pasty
Colour:	Black
Odour:	Slight of epoxy

pH-Value:

Changes in the physical state

n.d.

Test method



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX H COMP. A			
Revision date: 12.05.2020	Product code: 00359-1013	Page 5 of 9	
Melting point:	n.d.		
Initial boiling point and boiling range:	n.d.		
Sublimation point:	n.a.		
Softening point:	n.d.		
Flash point:	> 252 °C		
Flammability			
Solid:	n.a.		
Gas:	n.a.		
Explosive properties The product is not explosive.			
Lower explosion limits:	n.d.		
Upper explosion limits:	n.d.		
Ignition temperature:	> 300 °C		
Auto-ignition temperature			
Solid: Gas:	n.a. n.a.		
Decomposition temperature:	n.d.		
Oxidizing properties			
Not oxidising.			
Vapour pressure:	n.d.		
Density (at 20 °C):	1,26 g/cm³		
Bulk density:	n.a.		
Water solubility:	Immiscible		
(at 20 °C) Solubility in other solvents			
n.d.			
Partition coefficient:	n.d.		
Viscosity / dynamic:	n.d.		
Viscosity / kinematic:	n.d.		
Flow time:	n.d.		
Vapour density:	n.d.		
Evaporation rate:	n.d.		
Solvent separation test:	0 %		
Solvent content:	0 %		
9.2. Other information			
No data available			

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents Reactions with amines.



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX H COMP. A

Revision date: 12.05.2020

Product code: 00359-1013

Page 6 of 9

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat. Protect against direct sun radiation. Polymerisation occurs when exposed to heat.

10.5. Incompatible materials

Strong oxidizing agents, Amines, Acids and bases.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met. No toxicological data available.

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (Formaldehyde, oligomeric reaction products with 1-chloro-2, 3-epoxypropane and phenol; bis-[4-(2,3-epoxipropoxi)phenyl]propane)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available. Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Not readily biodegradable.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX H COMP. A

Revision date: 12.05.2020

Product code: 00359-1013

Page 7 of 9

Further information

080409

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations. Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information

Land transport (ADR/RID)

UN 3082
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
9
III
9
M6
5 L / 30 kg
E1
3
90
-
UN 3082
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
9
III
9
M6



according to Regulation (EC) No 1907/2006

Т	P TOP REMAF	IX H COMP. A	
Revision date: 12.05.2020	Product code:	00359-1013	Page 8 of 9
Limited quantity: Excepted quantity:	5 L / 30 kg E1		
Marine transport (IMDG)	UN 3082		
<u>14.1. UN number:</u> 14.2. UN proper shipping name:		LLY HAZARDOUS SUBSTANCE, LIQUID, N.O	20
14.2. On proper snipping hame.	(Epoxy resin)	LET HAZARDOUS SUBSTANCE, EIQUID, N.C	5.3.
<u>14.3. Transport hazard class(es):</u>	9		
14.4. Packing group:	111		
Hazard label:	9		
••••••••••••••••••••••••••••••••••••••	9		
Marine pollutant: Limited quantity:	Yes 5 L / 30 kg		
Excepted quantity:	E1		
EmS:	F-A, S-F		
Air transport (ICAO-TI/IATA-DGR)			
<u>14.1. UN number:</u>	UN 3082		
14.2. UN proper shipping name:	ENVIRONMENTA (Epoxy resin)	LLY HAZARDOUS SUBSTANCE, LIQUID, N.C	D.S.
<u>14.3. Transport hazard class(es):</u>	9		
14.4. Packing group:	III		
Hazard label:	9		
Limited supplity Decempon			
Limited quantity Passenger: Passenger LQ:	30 kg G Y964		
Excepted quantity:	E1		
IATA-packing instructions - Passenger:		964	
IATA-max. quantity - Passenger:		450 L	
IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:		964 450 L	
<u>14.5. Environmental hazards</u>			
ENVIRONMENTALLY HAZARDOUS:	ves	\wedge	
	,	¥.2	

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC):

0 %



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX H COMP. A				
Revision date: 12.05.2020	Product code: 00359-1013	Page 9 of 9		
Information according to 2012/18/EU (SEVESO III):	E2 Hazardous to the Aquatic Environment			
National regulatory information				
Employment restrictions:	Observe restrictions to employment for juveniles a work protection guideline' (94/33/EC). Observe en under the Maternity Protection Directive (92/85/EE nursing mothers.	nployment restrictions		

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intér IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Revision No: 1,2