




// ONE BRAND // ONE SOURCE // ONE SYSTEM



REMALOX HD

Optimum Impact and Wear Protection


Our high-quality REMALOX HD segmental plates offer you optimum impact and wear protection. Avoiding unnecessary maintenance and repair costs, they multiply the economic efficiency of your machines and plants several times.

REMALOX HD

CERAMIC/RUBBER LINING MATERIAL

REMALOX HD is a combination of highly wear-resistant 92 % Al₂O₃ ceramic elements hot-vulcanized in special rubber on a 5 mm steel backing plate S235 (St-37) which allows secure fixing by stud welding.

Available in 3 different thicknesses (35 mm, 55 mm, 75 mm).



REMALOX HD

Advantages:

- Extremely high abrasion resistance
- Absorption of impact energies
- Easy, flexible and quick installation with secure fixing
- Reduction of operating costs
- Long service life increases plant availability
- Easy exchange
- Good weather resistance

Typical fields of application:

- For applications exposed to abrasion wear, in particular at high conveying speeds
- For material transports with a small impact angle
- Medium-heavy to light applications in mining, quarries, sand and gravel plants and in the industry
- e.g. vibrating chutes, skips, bunkers, loading points, channels, funnels, silos, and the like that are exposed to abrasion wear

Technical specifications

Polymer basis	NR/BR/SBR	DIN ISO 1629
Specific weight	1.12 g/ccm	DIN EN ISO 1183-1
Hardness	62 Shore A	DIN ISO 7619-1
Colour	Black	

Art. No.	Designation	Dimensions	Dimensions ceramic element	Weight
539 9000	REMALOX HD 35	35 x 300 x 300 mm	Ø 20 x 20 mm	9.8 kg
539 8970	REMALOX HD 35	35 x 250 x 500 mm	Ø 20 x 20 mm	13.7 kg
539 8920	REMALOX HD 35	35 x 400 x 400 mm	Ø 20 x 20 mm	17.3 kg
539 8970	REMALOX HD 35	35 x 500 x 500 mm	Ø 20 x 20 mm	26.7 kg
539 3800	REMALOX HD 55	55 x 250 x 500 mm	Ø 20 x 35 mm	28.6 kg
539 3810	REMALOX HD 55	55 x 500 x 500 mm	Ø 20 x 35 mm	56.8 kg
539 3215	REMALOX HD 75	75 x 250 x 500 mm	Ø 20 x 50 mm	26.8 kg
539 3200	REMALOX HD 75	75 x 300 x 600 mm	Ø 20 x 50 mm	38.7 kg
539 3370	REMALOX HD 75	75 x 500 x 500 mm	Ø 20 x 50 mm	59.8 kg



REMA TIP TOP AG
 Gruber Strasse 65 · 85586 Poing /Germany
 Phone: +49 8121 707-100
 Fax: +49 8121 707-10 222
 info@tiptop.de
www.rema-tiptop.com



Your local contact